

/ LW03-01-32-260 CLAMPSTICK - EXTERNAL ROD



See online
technical sheet



/ Standards

- CEI 60855-1
- ASTM F711
- IEC 60832-1
- ASTM F1825

/ Use

The clampstick is the most universal tool used to install and remove personal protective grounding clamps, to install plastic and rubber cover-up equipment, etc.

Insulating tube, fiberglass over the foam core.



Control rod is also made of insulating material.

High-performance plastic pole head with integrated and replaceable hook.

/ Advantages

- Lighter
- A solution for all tensions
- Varnish finish
- High mechanical strength

/ Areas of activity

-  Electrical distribution
-  Transport

/ Technical specifications

- Pole kind : Fixed
- Operating voltage (V) : HTA (1 000 V to 50 000 V), HTB (> 50 000 V)
- Pipe kind : Rounded
- Pole weight (kg) : 3,2
- Pole weight (pounds) : 7,1
- Pipe diameter (mm) : 32
- Pipe diameter (inch) : 1" 1/4
- Color : Red
- Pole finition (terminal element) : Polish
- Total length (m) : 2,60
- Total length (inch) : 8'6"
- Longueur isolante (m) : 1,15
- Insulating length (inch) : 3'9"
- Rod diameter (mm) : 10
- Rod diameter (inch) : 2/5