

/ MF3/60


Multifunction tool for outer sheath, peelable semiconductor and insulation



See online technical sheet

/ Standards

- ENEDIS



/ Use

The MF3/60 tools enables the user to :

Remove the outer sheath (PE-PVC-PR) with a straight and neat cut





Score the peelable semiconductor (with the SR scoring stylus delivered with the tool)

Set the length to be removed and remove the insulation with a straight and neat cut

/ Advantages

- Smooth finish
- Heavy duty
- Easy to get to grips with

/ Areas of activity

-  Cable & Connections
-  Substation
-  Electrical distribution
-  Industry

/ Technical specifications

- Specific tools : Cable tools
- Cable tools : Cable tools
- Operating voltage (V) : HTA (1 000 V to 50 000 V)
- Packaging : Carton box
- Weight (kg) : 1.75
- Length (mm) : 305
- Width (mm) : 115
- Height (mm) : 165
- Max diameter (mm) : 58
- Mini diameter (mm) : 16
- Limit stop : None
- Stylet inclus : SR
- Remaining length of semi conductor (MIN) (mm) : 30
- Profondeur d'incision sur semi pelable : 0,4 / 0,7 / 0,9 / 1,1
- Scoring depth MAX (mm) : 1.5
- Cutting depth (max) on insulation : 7

/ Spare parts

	Reference	Designation
	LMF2	Blade for outer sheath and primary insulation